

Turbocharger system air leaks

The turbocharger forces extra air into the engine's combustion chamber, increasing engine efficiency and power output. The turbo operates in demanding conditions, and relies on various systems in the vehicle. Regular vehicle service is of crucial importance for the turbo's vitality and proper charge system functioning. Nissens offers advice on turbo system air leaks.



Impaired tightness of the ducts that channel air within the turbo circuit is one of the major problems affecting the turbocharged system's functionality.

Air leaks occur both on the vacuum side, i.e. from the air intake to the turbo inlet or on the system pressure side, i.e. from the turbo outlet to the engine intake manifold. In either case, leaks lead to air supply shortages in the charge system and will generate various problems. The major issue is underboost condition, where the system is unable to generate the requested charge air pressure. This leads to a significant decrease of the engine performance.

Engine operation can be set out of balance as faulty air supply disturbs the air-fuel ratio, causing incorrect combustion or impaired fuel economy. Additionally, various sensors such as MAF/MAP/Back pressure sensor will measure incorrect values, resulting in further errors registered by the ECU, possibly setting the engine into limp mode.

Porosity of aged rubber hoses, hose cracks, mechanical damage, including friction and heat impact, as well as loose clamps and unsealed connections, are the most common root causes for the charge system leaks. Air leaks in the system cause an increased load on the turbo, provoking over-speeding and premature, catastrophic failure.

Recommended Solution

Check if the system delivers proper boost pressure and see if any system underboost is related to leak problems.

If you suspect a leak, inspect the entire air duct circuit within the turbo system. A dedicated

leak test, using pressurised air, is one of the most efficient and recommended procedures to spot leaks. When testing, control the entire path from the air filter box, throughout turbo hoses, intercooler and engine intake manifold. Make sure all piping is in proper condition, free of cracks and tears and that all connections and clamping is tight. Replace/repair them if necessary.

Common Symptoms of Air Leaks in the Turbocharger System

- Significant decrease of engine power
- Lag in engine response – longer turbo lag than normal
- Black smoke from exhaust
- Whistling noise from the engine compartment
- Abnormal noises from the engine
- Increased fuel consumption
- Severe mechanical turbo failures, mainly due to overspeeding (collapsing compressor wheel, broken shaft, etc.)
- Engine enters limp mode, underboost errors registered e.g. P0299, P2263

Diagnostic Tips

Control the system boost level - Measure the boost level generated during the full engine load. Compare the data with the vehicle documentation. Lack of proper boost may relate to leakages. Boost pressure can be measured by means of a pressure gauge or if possible, by on-board diagnostics and live data of the boost.

Perform a holistic diagnostics of the charge system - Proper operation of the charge system relies on various components. Underboost

errors may also have other causes than leaks.

Potential factors related to underboost errors:

- Air channel inner restrictions
- Turbocharger failures (waste-gate valve failures or vane failures)
- Faulty metering devices – boost pressure, MAP, MAF, back-pressure, IPC sensors
- Turbocharger control device failures – actuators, boost controllers
- EGR system faults

Charge System Tightness Test

Pressure testing the charge air system is an effective and inexpensive method for locating leaks. Make your own test kit or choose a kit option available for the automotive market.

The pressure testing method is based on capping air ducts and filling the charge system with air. A cap must tightly seal one side of the tested circuit. At the other side, a cap including an air valve to introduce the test air, must be sealed. When the pressure inside builds up, it is very easy to spot leakages.

1. Depending on the vehicle model and system layout, you can either test the entire duct system starting from air filter box throughout the turbo, intercooler and engine manifold or test the system intake (vacuum) and pressure sides separately. Remember to disconnect and seal possible air channels that may be connected to the charge intake/pressure sides (e.g. crankcase ventilation etc.).
2. Do not pressurise the system by more than 2 Bars/30 PSI
3. Increase the pressure gradually, starting at 0.5 Bar/7 PSI
4. Be careful when working with pressurised air, loose caps/clamps or connections may pop off and seriously injure you or damage the vehicle.
5. Look/listen for hissing noises at hoses and connections. You can use a soapy-water solution sprayed on the potential leak spots to facilitate leak finding.
6. If leaks cannot be concluded immediately, leave the circuit filled with air and observe for possible pressure drops on the gauge of the pressurizing equipment.
7. By end of the test, release the pressure slowly to empty the system.

Nissens®
DELIVERING THE DIFFERENCE